

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A method for analyzing a sample containing particles to detect and characterize target particles having a plurality of detectable characteristics in a fixed volume capillary that contains a fluorescent background and which exhibits background characteristics, the method comprising:

5 (a) scanning the fixed volume capillary containing the sample to generate a plurality of channels of data, wherein each channel of data comprises a distinct detectable characteristic and a distinct background characteristic;

(b) sampling each of the channels of data to produce corresponding sets of pixel values;

10 (c) generating sets of enhanced pixel values by independently modifying each set of pixel values to selectively enhance spatial features that are indicative of a target particle;

(d) removing from one or more sets of enhanced pixel values the distinct background characteristic for the corresponding channel;

15 (e) independently establishing threshold values for the detection of said particles for each set of enhanced pixel values;

(f) independently identifying, in each set of enhanced pixel values, groups of above-threshold pixels located in patterns that are diagnostic of said particles;

20 (g) independently identifying, for each group of above-threshold pixels located in a diagnostic pattern in a particular set of enhanced pixel values, the corresponding below-threshold or at-threshold pixels in the remaining sets of enhanced pixel values; [[and]]

(h) characterizing the target particles in the sample by analyzing the pixels

independently identified in steps (f) and (g); and

(i) calculating at least one of:

25 (I) a volume of the sample scanned; and

(II) an absolute particle count;

~~whereby~~ wherein particles are initially identified and analyzed in channels with
above-threshold pixels located in patterns diagnostic of said particles, and said particles
are then independently analyzed in all remaining channels by locating pixels in the same
30 positions as the above-threshold pixels initially identified.

2. (Currently Amended) [[In a]] A method for analyzing a sample containing
particles to detect and characterize target particles having a plurality of detectable
characteristics in a fixed volume capillary that contains a fluorescent background and
which exhibits background characteristics, the method comprising:

5 (a) scanning the fixed volume capillary containing the sample to generate a
plurality of channels of data, wherein each channel of data comprises a distinct detectable
characteristic and a distinct background characteristic;

 (b) sampling each of the channels of data to produce corresponding sets of source
pixel values;

10 (c) summing the sets of source pixel values to generate a composite image;

 (d) calculating a threshold for particle detection in said composite image
independently in each set of source pixel values;

 (e) performing particle detection in said composite image using said threshold
independently in each set of source pixel values using the corresponding threshold;

15 (f) identifying, for each particle identified in a particular set of source pixel
values in step (e), the corresponding pixels in the remaining sets of source pixel values;

[[and]]

(g) analyzing the pixels identified in step (f); and

(h) calculating at least one of:

20

(I) a volume of the sample scanned; and

(II) an absolute particle count.

3. (Currently Amended) [[In a]] A method for analyzing a sample containing particles to detect target particles having a plurality of detectable characteristics in a fixed volume capillary that contains a fluorescent background and which exhibits background characteristics, the method comprising[[:]]:

5

(a) scanning the fixed volume capillary containing the sample to generate a plurality of channels of data, wherein each channel of data comprises a distinct detectable characteristic and a distinct background characteristic;

(b) sampling each of the channels of data to produce corresponding sets of source pixel values;

10

(c) calculating a threshold for particle detection independently in each set of source pixel values without first summing the source images; [[and]]

(d) performing particle detection independently in each set of source pixel values using the corresponding threshold; and

(e) calculating at least one of:

15

(I) a volume of the sample scanned; and

(II) an absolute particle count.